



Una empresa **Bayer** 



Carta de colores · Colour chart
Cemento Cement

Oxined[®]

Cemento blanco White cement



1 Amarillo / Yellow 2%



413 Amarillo / Yellow 2%



875 Amarillo / Yellow 2%



7010 Pardo / Brown 2%



7012 Pardo / Brown 2%



7222 Pardo / Brown 2%



7C22 Pardo / Brown 2%



2477 Rojo / Red 2%



2583 Rojo / Red 2%



2714 Rojo / Red 2%



3 Amarillo / Yellow 2%



840 Amarillo / Yellow 2%



7001 Naranja / Orange 2%



9 Pardo / Brown 2%



7025 Pardo / Brown 2%



7235 Pardo / Brown 2%



2584 Rojo / Red 2%



2785 Rojo / Red 2%



4130B Rojo / Red 2%



2626 Rojo / Red 2%




909 Amarillo / Yellow 2%



191 Amarillo / Yellow 2%



8C40 Amarillo / Yellow 2%



7415 Pardo / Brown 2%



6920 Pardo / Brown 2%



6926 Pardo / Brown 2%



6C19 Pardo / Brown 2%



6C61 Pardo / Brown 2%



6913 Pardo / Brown 2%



6943 Pardo / Brown 2%



7426 Pardo / Brown 2%



6919 Pardo / Brown 2%



6916 Pardo / Brown 2%



6924 Pardo / Brown 2%



6990 Pardo / Brown 2%



6928 Pardo / Brown 2%



6C27 Pardo / Brown 2%



6935 Pardo / Brown 2%



6C13 Pardo / Brown 2%



6947 Pardo / Brown 2%



6992 Pardo / Brown 2%



6998 Pardo / Brown 2%



6C21 Pardo / Brown 2%



6C90 Pardo / Brown 2%



6978 Pardo / Brown 2%



6C43 Pardo / Brown 2%



6911 Pardo / Brown 2%



6C11 Pardo / Brown 2%



5820 Negro / Black 2%



(*) 7 Gris / Gray 2%



6994 Pardo / Brown 2%



6996 Pardo / Brown 2%



6C94 Pardo / Brown 2%



6956 Pardo / Brown 2%



6959 Pardo / Brown 2%



6C52 Pardo / Brown 2%



6952 Pardo / Brown 2%



(*) 12A Negro / Black 1%



5831 Negro / Black 2%



AS Verde / Green 2%

Las tonalidades que muestra el apartado de "cemento blanco" son las conseguidas con la gama general fabricada por Europigments. De entre ellos hemos seleccionado algunos tipos para diferenciar cual sería el resultado de su adición a un cemento gris de tonalidad media.

The shades displayed in the "white cement" section are those achieved with the standard range manufactured by Europigments. From these we have selected a number of pigments in order to show the result of their addition to a mid-shade gray cement.

(*) Pigmentos con limitaciones en su empleo en el exterior.

(*) Pigments with limitations when used outdoors.

Cemento gris Gray cement



1 Amarillo / Yellow 2%



6C19 Pardo / Brown 2%



7001 Naranja / Orange 2%



2626 Rojo / Red 2%



2477 Rojo / Red 2%



6C43 Pardo / Brown 2%



5831 Negro / Black 2%



(*) 12A Negro / Black 1%



AS Verde / Green 2%



B52 Blanco / White 2%



El color que muestra cada pastilla ha sido elaborado con tintas especiales, tomando como referencia aplicaciones de los pigmentos en cemento blanco o gris, según el caso.

En la parte inferior de cada pastilla se pueden ver, por este orden, el número de referencia, la descripción del color y su porcentaje de adición referido al peso de cemento.

Hay que añadir que, variando el porcentaje de adición del pigmento, podemos modificar la presencia del mismo, pudiendo conseguir desde tonalidades pastel hasta colores saturados.

Los pigmentos cuyas referencias van precedidas de un asterisco (*) tienen, en su composición, algún elemento inestable si se exponen a la intemperie.

Debido a la gran diversidad de productos derivados del cemento, las posibles combinaciones de éste con otros elementos (áridos, cargas, cal, etc...), y a la infinidad de acabados superficiales, la presente carta de colores debe de considerarse como meramente orientativa, siendo necesario el ensayo de cada pigmento en condiciones reales para obtener una aproximación real a lo que será su posterior aplicación industrial.

The colour shown in each tablet has been produced using special dyes, taking as reference applications of the pigments in either white or grey cement.

Below each tablet can be seen, in this order, the reference number, colour and percentage added by weight of cement.

It must be pointed out that, by varying the percentage of pigment added, we can modify its appearance to enable us to achieve shades ranging from pastel to rich tones.

The pigments whose reference numbers are preceded by an asterisk () contain, in their composition, elements liable to instability if exposed to adverse weather conditions.*

Given the wide range of products derived from cement, its possible mixture with other components (aggregates, lime, etc.), and the infinity of surface finishes, the colour chart shown here should only be taken as a guide. To obtain a reliable indication as to its subsequent industrial application each pigment must be tested under real conditions.